

NONMETALLIC LIQUID-TIGHT CONDUIT & FITTING



NONMETALLIC LIQUID-TIGHT FLEXIBLE CONDUIT

- Material : Poly Vinyl Chloride (PVC)
UV resistant & Flame retardant
- Resists sunlight, corrosion, abrasion, oil, water, acid, metal shavings and rough environments.”
- For direct burial and incased in concrete.
- Temperature range : 80°C dry, 60°C wet, 70°C oil
- For the installation and protection of electrical conductors in circuits of 600V nominal, or less.
- Available color : Dark grey (A), light grey (B)

Item No.	Trade Size (inch)	Interior Dia. (mm)	Outside Dia. (mm)	Length (feet)
NLT-03899G	3/8	12.3	17.8	100
NLT-05099G	1/2	16.1	21.1	100
NLT-07599G	3/4	21.1	26.4	100
NLT-10099G	1	26.6	33.1	100
NLT-12520G	1 1/4	35.1	41.6	20
NLT-15020G	1 1/2	40.1	47.7	20
NLT-20020G	2	51.5	59.7	20

NONMETALLIC LIQUID-TIGHT WHIP

- Material : Poly Vinyl Chloride (PVC)
UV resistant & Flame retardant
- 600-Volt 10AWG stranded copper THHN/THWN insulated singles (black and red), green insulated copper grounding conductor.
- With straight & 90° connectors installed.
- Resists sunlight, corrosion, abrasion, oil, water, acid, metal shavings and rough environments.”
- Temperature range : 80°C dry, 60°C wet, 70°C oil
- Applications : Air condition unit hook up, heat pumps, pools, SPA, outdoor lighting, motors, solar panels.

With Plastic (Nylon) Connectors

NLTW-504GP	1/2", Grey, Cable Length 4 feet
NLTW-506GP	1/2", Grey, Cable Length 6 feet
NLTW-754GP	3/4", Grey, Cable Length 4 feet
NLTW-756GP	3/4", Grey, Cable Length 6 feet

With Metallic (Zinc-Alloy) Connectors

NLTW-504GM	1/2", Grey, Cable Length 4 feet
NLTW-506GM	1/2", Grey, Cable Length 6 feet
NLTW-754GM	3/4", Grey, Cable Length 4 feet
NLTW-756GM	3/4", Grey, Cable Length 6 feet

* Available length 4, 6, 8 feet or others under request





NONMETALLIC LIQUID-TIGHT STRAIGHT CONNECTOR

- Material : Nylon, UV resistant & Flame retardant
- Resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents.
- For nonmetallic liquid-tight flexible conduit.

NLSC038	3/8"
NLSC050	1/2"
NLSC075	3/4"
NLSC100	1"
NLSC125	1 1/4"
NLSC150	1 1/2"
NLSC200	2"

NONMETALLIC LIQUID-TIGHT 90° CONNECTOR

- Material : Nylon, UV resistant & Flame retardant
- Resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents.
- For nonmetallic liquid-tight flexible conduit.

NLIC038	3/8"
NLIC050	1/2"
NLIC075	3/4"
NLIC100	1"
NLIC125	1 1/4"
NLIC150	1 1/2"
NLIC200	2"

