



RESIDUAL CIRCUIT DEVICE (RCD / GFCI)

- German System : IEC61543 / HP639 S1 Standard
- Housing Material : Polycarbonate
- Spec. : 230/50Hz 16A 3600W 10mA IP20; 30mA IP54
With Reset & Test Push Button
- Size : 120*54*65 (mm)
- GS (TUV), CE Approved & RoHS

RCD03.10 Schuko RCD Adaptor With Cover 10mA
RCD03.30 Schuko RCD Adaptor With Cover 30mA

RESIDUAL CIRCUIT DEVICE (RCD / GFCI)

- German & UK System : IEC61543 / HP639 S1 Standard
- Housing Material : Polycarbonate
- Spec. : 230/50Hz 16A 3600W 30mA IP54
240/50Hz 13A 3120W 30mA IP54
With Reset & Test Push Button
- Size : 106*50*65 (mm)
- GS (TUV), CE, RoHS; BS7071, BS1363 Approved

RCD01G.30 Schuko RCD Plug 30mA
RCD01B.30 UK RCD Plug 30mA



PORTABLE RESIDUAL CIRCUIT DEVICE (IN-LINE PRCD / GFCI)

- European System : IEC61543 / HP639 S1 Standard
- Housing Material : Polycarbonate
- Spec. : 110-130V AC 16A 10mA/30mA IP55
220-240V AC 16A 10mA/30mA IP55
With Reset & Test Push Button
- Size : 185*55*45 (mm)
- GS (TUV), CE Approved & RoHS

RCD051.30 Wire Connection PRCD With Cover 30mA 110-130V
RCD052.30 Wire Connection PRCD With Cover 30mA 220-240V



PORTABLE RESIDUAL CIRCUIT DEVICE (IN-LINE PRCD / GFCI)

- European System : IEC61543 / HP639 S1 Standard
- Housing Material : Polycarbonate
- Spec. : 110-130V AC 16A 10mA/30mA IP66
220-240V AC 16A 10mA/30mA IP66
With Reset & Test Push Button
- Size : 190*57*57 (mm)
- BG, SEMKO, CE Approved & PAHS

RCDG16C.10 Wire Connection PRCD 10mA 250V
RCDG16C.30 Wire Connection PRCD 30mA 250V

